

White
Gray
Black

0.3 kg

Ø 75 [mm]

Material

Trim	AL. DIE-CASTING
Mounting Cover	AL. DIE-CASTING (TILT ∠ 20 º)
Heat Sink	AL. DIE-CASTING
Reflector	PC (Vacuum Coating)
Size	Ø 85 x H 58 [mm]
Hole Cut	Ø 75 [mm]

Description	COB TYPE		
Input Power	10 W		
Output Power	8 W		
Luminous Flux	3 000 K	27.1 º	910 lm
		37.7 º	999 lm
Color Temperature	4 000 K / 3 000 K		
Color Rendering Index (CRI)	80 / 90		
Operating Temperature Range	-20 to +40 ℃		
SDCM	3 Step		

Driver

Input Voltage Range	220-240 Vac , 50/60 Hz
Output Current	250 mA
Output Voltage	33 Vdc
Power Factor	0.9 이상
Drive Lifetime	50 000 Hours
Maintenance of Lumen -L80	50 000 Hours at 25 ℃

CCT MULTIPLIERS

	CRI 80	CRI 90
2 700 K	x 0.96	x 0.81
3 000 K	x 1.00	x 0.85
3 500 K	x 1.03	x 0.88
4 000 K	x 1.06	x 0.91

[3 000 K / CRI 80]



910 lm



999 lm