

- White
- Gray
- Black

0.7 kg

Ø 100 [mm]

Material

Trim	AL. DIE-CASTING
Heat Sink	AL. DIE-CASTING
Adjustable ring	PC (Tilt ∠ 30°)
Reflector	CHROME (Non Glare Refelctor)
Size	Ø 113 x H 137 [mm]
Hole Cut	Ø 100 [mm]

Description	COB TYPE
Input Power	19 W
Output Power	16 W
Luminous Flux	3 000 K 14.2 ° 881 lm 21.7 ° 774 lm 32.5 ° 1 019 lm
Color Temperature	4 000 K / 3 000 K
Color Rendering Index (CRI)	80 / 90
Operating Temperature Range	-20 to +40 °C
SDCM	3 Step

Driver


Input Voltage Range	220-240 Vac , 50/60 Hz
Output Current	450 mA
Output Voltage	35 Vdc
Power Factor	0.9 이상
Drive Lifetime	50 000 Hours
Maintenance of Lumen -L80	50 000 Hours at 25 °C

Option **IP44**


CCT MULTIPLIERS

	CRI 80	CRI 90
3 000 K	x 1.00	x 0.85
4 000 K	x 1.06	x 0.91


[3 000 K / CRI 80]



881 lm



774 lm



1 019 lm