

- White
- Gray
- Black

1.9 kg

W 170 x D 170 [mm]

Material

Trim	AL. DIE-CASTING
Heat Sink	AL. DIE-CASTING
Reflector	AL. ANODIZED SPECULAR SILVER
Size	W 186 x D 186 x H 199 [mm]
Hole Cut	W 170 x D 170 [mm]

Description

Description	COB TYPE		
Input Power	28 W		
Output Power	24 W		
Luminous Flux	3 000 K	17.8 °	3 044 lm
		26.0 °	3 000 lm
		39.2 °	3 056 lm
Color Temperature	4 000 K / 3 000 K		
Color Rendering Index (CRI)	80 / 90		
Operating Temperature Range	-20 to +40 °C		
SDCM	3 Step		


Driver

Input Voltage Range	220-240 Vac , 50/60 Hz
Output Current	700 mA
Output Voltage	35 Vdc
Power Factor	0.9 이상
Drive Lifetime	50 000 Hours
Maintenance of Lumen -L80	50 000 Hours at 25 °C


CCT MULTIPLIERS

	CRI 80	CRI 90
3 000 K	x 1.00	x 0.85
4 000 K	x 1.06	x 0.91


[3 000 K / CRI 80]



3 044 lm



3 000 lm



3 056 lm