

- White
- Gray
- Black

5.8 kg

W 430 x D 170 [mm]

Material

Trim	AL. DIE-CASTING
Heat Sink	AL. DIE-CASTING
Reflector	AL. ANODIZED SPECULAR SILVER
Size	W 445 x D 186 x H 199 [mm]
Hole Cut	W 430 x D 170 [mm]

Description

Description	COB TYPE
Input Power	28 W x 3
Output Power	24 W x 3
Luminous Flux	3 000 K 17.8 ° 3 044 lm x 3
	26.0 ° 3 000 lm x 3
	39.2 ° 3 056 lm x 3
Color Temperature	4 000 K / 3 000 K
Color Rendering Index (CRI)	80 / 90
Operating Temperature Range	-20 to +40 °C
SDCM	3 Step


Driver

Input Voltage Range	220-240 Vac , 50/60 Hz
Output Current	700 mA x 3
Output Voltage	35 Vdc
Power Factor	0.9 이상
Drive Lifetime	50 000 Hours
Maintenance of Lumen -L80	50 000 Hours at 25 °C


CCT MULTIPLIERS

	CRI 80	CRI 90
3 000 K	x 1.00	x 0.85
4 000 K	x 1.06	x 0.91


[3 000 K / CRI 80]



3 044 lm x 3



3 000 lm x 3



3 056 lm x 3