

- White
- Gray
- Black

0.8 kg

Ø 130 [mm]

Material

Trim	AL. DIE-CASTING
Adjustable Ring	AL. DIE-CASTING (TILT \angle 25 °)
Mounting Ring	AL. EXTRUDE
Heat Sink	AL. DIE-CASTING
Reflector	LENS
Size	Ø 140 x H 172 [mm]
Hole Cut	Ø 130 [mm]

Description	COB TYPE		
Input Power	20 W		
Output Power	16 W		
Luminous Flux	3 000 K	19.7 °	2 078 lm
		32.4 °	2 131 lm
		48.5 °	2 025 lm
Color Temperature	4 000 K / 3 000 K		
Color Rendering Index (CRI)	80 / 90		
Operating Temperature Range	-20 to +40 °C		
SDCM	3 Step		


Driver

Input Voltage Range	220-240 Vac , 50/60 Hz
Output Current	500 mA
Output Voltage	34 Vdc
Power Factor	0.9 이상
Drive Lifetime	50 000 Hours
Maintenance of Lumen -L80	50 000 Hours at 25 °C


CCT MULTIPLIERS

	CRI 80	CRI 90
3 000 K	x 1.00	x 0.85
4 000 K	x 1.06	x 0.91


[3 000 K / CRI 80]



2 078 lm



2 131 lm



2 025 lm