

- White
- Gray
- Black

1.0 kg

W 265 x D 100 [mm]

Material

Trim	AL. DIE-CASTING
Adjustable Ring	AL. DIE-CASTING (TILT \angle 20 °)
Mounting Ring	AL. DIE-CASTING
Heat Sink	AL. DIE-CASTING
Reflector	PC (Vacuum Coating)
Size	W 274 x D 108 x H 76 [mm]
Hole Cut	W 265 x D 100 [mm]

Description	COB TYPE
Input Power	10 W x 3
Output Power	8 W x 3
Luminous Flux	3 000 K 15.4 ° 930 lm x 3
	28.3 ° 901 lm x 3
	41.4 ° 931 lm x 3
Color Temperature	4 000 K / 3 000 K
Color Rendering Index (CRI)	80 / 90
Operating Temperature Range	-20 to +40 °C
SDCM	3 Step


Driver

Input Voltage Range	220-240 Vac , 50/60 Hz
Output Current	250 mA
Output Voltage	34 Vdc
Power Factor	0.9 이상
Drive Lifetime	50 000 Hours
Maintenance of Lumen -L80	50 000 Hours at 25 °C


CCT MULTIPLIERS

	CRI 80	CRI 90
3 000 K	x 1.00	x 0.85
4 000 K	x 1.06	x 0.91


[3 000 K / CRI 80]



930 lm x 3



901 lm x 3



931 lm x 3